

Moxa Inc.

13F, No. 3, Sec. 4, New Taipei Blvd., Xinzhuang Dist. New Taipei City 242032, Taiwan, R.O.C.

Tel: +886-2-8919-1230 Fax: +886-2-8522-8623 www.moxa.com

Product Discontinuance Notification—PDN#0000383886

March 07, 2023

Dear Valued Customer,

We would like to inform you that Moxa is going to discontinue the **ioLogik E4200** and **ioLogik 4000 M-Series modules**. This process will begin **Mar 31, 2023**.

If you need any of these discontinued products for an existing project, please contact your Moxa sales representative to place orders before **Dec 31, 2023**. Also, please note that last-buy orders may be subject to availability.

Please review the details below to determine how these discontinuances will affect your products and/or operations.

Which products will be discontinued?

The following products will be discontinued. Also, see the models recommended to replace the soon to-be-discontinued models, as well as when the replacement models will be available for order.

Replacement 1 – For pure I/O application (no Click & Go or MX-AOPC UA Active tags)

Discontinued	Recommended Replacement	Available for Order
ioLogik E4200	ioThinx 4510	Available Now
ioLogik 4000 (M) Series Modules	ioThinx 4500 Series (45MR) Modules	Available Now

ioLogik 4000 Series (M) Modules		ioThinx 4500 Series (45MR) Modules		
DC - Digit	DC - Digital Input Modules			
M-1600	16 Dls, 24VDC, sink (PNP type)	45MR-1600	46 Pla 04VPO aliala (PNP 6 ma)	
M-1800	8 DIs, 24VDC, sink (PNP type)		16 Dls, 24VDC, sink (PNP type)	
M-1601	16 DIs, 24VDC, source (NPN type)	45MR-1601	46 Dia 24VDC agurea (NDN tree)	
M-1801	8 DIs, 24VDC, source (NPN type)	45WIK-1601	16 Dls, 24VDC, source (NPN type)	
AC - Digit	AC - Digital Input Modules			
M-1450	4 DIs, 110 VAC	N/A	N/A	
M-1451	4 DIs, 220 VAC	N/A	N/A	
Digital Output Modules				
M-2600	16 DOs, 24VDC, sink type	45MR-2600	16 DOs, 24VDC, sink type	
M-2800	8 DOs, 24VDC, sink type			
M-2601	16 DOs, 24VDC, source type	45MR-2601	16 DOs, 24VDC, source type	

Form number: HQ-PD.150 Version: 2.1 Page 1/3



Moxa Inc.

13F, No. 3, Sec. 4, New Taipei Blvd., Xinzhuang Dist. New Taipei City 242032, Taiwan, R.O.C. Tel: +886-2-8919-1230

Fax: +886-2-8522-8623 www.moxa.com

			www.moxa.com	
M-2801	8 DOs, 24VDC, source type			
		45MR-2606	8 DIs, PNP type and 8 DOs, 24VDC, source	
	45MR-2606		type	
Relay Out	tput Modules			
M-2450	4 Relay, Form A	45MR-2404	4 Relays, Form A	
Analog In	put Modules			
M-3802	8 Als, 4 to 20 mA, 12-bit	45MR-3800	8 Als, 0 to 20mA/4 to 20mA, 16-bit	
M-3810	8 Als, 0 to 10V, 12-bit	45MR-3810	8 Als, -10 to 10V/0 to 10V, 16-bit	
Temperature Input Modules				
M-6200	2 RTDs	45MR-6600	6 RTDs	
M-6201	2 TCs	45MR-6810	8 TCs	
Analog Output Modules				
M-4402	4 AOs, 4 to 20 mA, 12-bit	45MD 4400	4 4 0 - 0 4 - 20 - 4 4 4 - 20 - 4 10 4 - 40 14 4 5 16 1	
M-4410	4 AOs, 0 to 10V, 12-bit	45MR-4420	4 AOs, 0 to 20mA/4 to 20mA/0 to 10V, 12-	
Others				
M-7001	System power module, 24 VDC, 11 to 28.8 VDC, 2 channels		System and field power module	
M-7002	Field power module, 5/24/48 VDC, 110/220 VAC, 1 channel	45MR-7210	System power: 12 to 48 VDC, 1 channel Field power: 12/24 VDC, 1 channel	
M-7804	Potential distributor module, 0 VDC, 8 channels	45MR-7820	Potential distributor module, 0 VDC,12/24	
M-7805	Potential distributor module, 24 VDC, 8 channels	49WK-702U	VDC, 8 channels	
	•			

Applicable differences in specifications

In this table, we list the difference in specifications between the discontinued products and the recommended replacement products.

Specification	ioLogik E4200 (Discontinued)	ioThinx 4510 (Replacement)
Dimensions (W*H*D)	45 x 99 x 70 mm (1.8 x 3.9 x 2.8 in)	42.3 x 99 x 75 mm (1.67 x 3.9 x 2.95 in)
Click & Go Logic	Supported	Not supported
MX-AOPC UA	Supported	Not supported
active tags		
Wiring	14 to 28 AWG	Serial cable, 16 to 28 AWG
	(Recommend 22 AWG)	Power cable, 12 to 18 AWG

Form number: HQ-PD.150 Page 2/3 Version: 2.1



Moxa Inc.

13F, No. 3, Sec. 4, New Taipei Blvd., Xinzhuang Dist. New Taipei City 242032, Taiwan, R.O.C. Tel: +886-2-8919-1230

Tel: +886-2-8919-1230 Fax: +886-2-8522-8623 www.moxa.com

Specification	ioLogik 4000 M-series (Discontinued)	45MR series (Replacement)
Dimensions (W*H*D)	12 x 99 x 70 mm (0.5 x 3.9 x 2.8 in)	17.5 x 99 x 60.5 mm (0.69 x 3.9 x 2.38
		in)
Wiring	14 to 28 AWG	18 to 24 AWG
	(Recommend 22 AWG)	(12 to 26 AWG for 45MR-7210)

Replacement 2 – For applications that need Click & Go or MX-AOPC Active tags

I/O < 20 channel:

Discontinued	Recommended Replacement	Available for Order
ioLogik E4200	ioLogik E2200 Series	Available Now
ioLogik 4000 (M) Series Modules		Available Now

I/O > 20 channel

Discontinued	Recommended Replacement	Available for Order
ioLogik E4200	ioLogik 2500 Series and ioLogik E1200	Available Now
ioLogik 4000 (M) Series Modules	Series	Available Now

(*Overall installation space should be considered regarding replacement 2)

Please note that all service rules (e.g., warranty) still apply to discontinued products.

If you have any questions, please contact **Steven Chen** at <u>stevency.chen@moxa.com</u>, or contact your regional sales representative.

Form number: HQ-PD.150 Version: 2.1 Page 3/3